

MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: Transformer Oil (0826)

Manufacturer Information:

Tulco Oils, Inc.

5240 E. Pine Street Tulsa, Oklahoma 74115

Product Use:

Industrial Oil

Emergency Phone Numbers:

Chemtrec N/A

Tulco Oils, Inc. (800) 375-2347

Information:

Product Safety Information (800) 375-2347

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
Light Naphthenic Hydrotreated Distillates BHT Blend Additives	64742-53-6 Proprietary	>98% >1%

EXPOSURE GUIDELINES (SEE	SECTION 15 F	OR ADDITIONAL EX	(POSURE LIMITS)	
	CAS No.	Governing Body	Exposure Limits	

3. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

Little or no immediate hazard.

Hazards Ratings:

Key: 0 = least, 1 = slight, 2 = moderate, 3 = high, 4 = extreme

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>PPI</u>
NFPA	1	1	0	
HMIS	1	1	0	X

• POTENTIAL HEALTH EFFECTS

PRE-EXISTING MEDICAL CONDITIONS

The following diseases or disorders may be aggravated by exposure to this product: Skin,

INHALATION

No acute effects expected.

LC50 (mg/l): no data LC50 (mg/m3): no data LC50 (ppm): no data

SKIN

Practically non-toxic if absorbed through the skin. May cause minimal skin irritation.

Draize Skin Score: no data Out of 8.0

LD50 (mg/kg): no data

EYES

No eye effect expected.

INGESTION

Practically non-toxic if ingested. **LD50** (g/kg): no data

4. FIRST AID MEASURES

INHALATION

No specific treatment is necessary since this material is not likely to be hazardous by inhalation. If exposed to excessive levels of dusts or fumes, remove to fresh air and get medical attention if cough of other symptoms develop.

SKIN

Wash with soap and water. Get medical attention if irritation develops or persists. Wash clothing before reuse.

EYES

Hold eyelids apart and flush eyes with plenty of water for at least 15 minutes. If eye irritation persists, obtain medical treatment.

INGESTION

Material is practically non-toxic. Induction of vomiting is not required. Get medical attention immediately.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA

Water spray Regular foam Dry chemical Carbon dioxide

FIRE FIGHTING INSTRUCTIONS

Wear structural fire fighting gear. As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

FLAMMABLE PROPERTIES

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point		300			F	COC
Autoignition Temperature				N/A	F	N/A
Lower Explosion Limit				no data	%	N/A
Upper Explosion Limit				no data	%	N/A

6. ACCIDENTAL RELEASE MEASURES

Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

7. HANDLING AND STORAGE

HANDLING

Wash thoroughly after handling.

STORAGE

NFPA class IIIB storage. Flash point is greater than 200 degrees F.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

ENGINEERING CONTROLS

Use with adequate ventilation. Ventilation is normally required when handling or using this product to keep exposure to airborne contaminants below the exposure limit. Mechanical ventilation recommended.

• PERSONAL PROTECTION

EYE PROTECTION

Safety glasses (with side shields) recommended. Splash proof chemical goggles are recommended to protect against the splash of product.

GLOVES or HAND PROTECTION

Protective gloves are recommended when prolonged skin contact cannot be avoided. The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Neoprene; Nitrile; Viton;

RESPIRATORY PROTECTION

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Respiratory protection is not usually needed unless product is heated or misted.. Half-mask air purifying respirator with dust / mist filters or HEPA filter cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with dust / mist filters or HEPA filter cartridges is acceptable for exposures to fifty (50) times the exposure limit. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH/MSHA-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

OTHER

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. Polyvinyl alcohol (PVA); The following materials are acceptable for use as protective clothing: Polyvinyl chloride (PVC); Neoprene; Nitrile; Viton; Polyurethane; Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, respiratory protection may be necessary and wear appropriate protective clothing to avoid contact with material.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Property	Typical	Units	Text Result	Reference
Appearance		N/A	Pale Straw/White	
Boiling Point		F	no data	
Bulk Density		lb/gal	no data	
Melting Point		F	no data	
Molecular Weight		g/mole	No data	
Octanol/Water Coefficient		N/A	no data	
pН		N/A	no data	
Specific Gravity		N/A		
Solubility In Water		wt %	NIL	
Odor		N/A	Light Bland	
Odor Threshold		ppm	no data	
Vapor Pressure		mmHg	<0.0001	@ 20 C
Viscosity (F)		SUS		@ 100 F
Viscosity (C)	9.01	CsT		@ 40 C

% Volatile wt % NIL

10. STABILITY AND REACTIVITY

STABILITY

Stable

CONDITIONS TO AVOID

Avoid heat, sparks and open flame.

INCOMPATIBILITY

Strong oxidizers

HAZARDOUS DECOMPOSITION PRODUCTS

Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.

HAZARDOUS POLYMERIZATION

Will not polymerize.

11. ECOLOGICAL INFORMATION

No data available

12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is not a RCRA hazardous waste, if not contaminated. If material has been "used", RCRA criteria (ignitability, reactivity, corrosivity and toxicity) must be determined. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

13. TRANSPORT INFORMATION

<u>Mode</u>	Proper Shipping Name			
Ground	Not Regulated			
	-			
<u>Mode</u>	Hazard Class	UN/NA No.	<u>Label</u>	
Ground	NI/A	NI/Δ	Not Pegulated	
	Ground Mode	Ground Not Regulated Mode Hazard Class	Mode Hazard Class UN/NA No.	Ground Not Regulated

14. REGULATORY INFORMATION

Regulatory List	Component	CAS No.

Title III Classifications Sections 311,312:

Acute: NOChronic: NOFire: NOReactivity: NO

Sudden Release of Pressure: NO

15. OTHER INFORMATION

Limits for the product- 5mg/m3, Oil Mist Limit, (OSHA PEL/ACGIH TLV) WHMIS Classification: not controlled. Please refer to the material safety data sheet for complete information.